



NORDIC TRANSDUCER



MP6Plus is a Professional Digital Laboratory Indicator with 1, 2, 3, or 4 inputs, suitable for receiving signals from strain gauge sensors, transmitters with voltage or current output and PT100. Particularly suitable for both static and dynamic applications, for calibration and verification in metrology laboratories or industrial environments where it is necessary to make measurements of weight, force, pressure, torque, displacement and temperature in a synchronized manner.

To FIT EVERY APPLICATION the instrument can be configured and customized: the function keys F1, F2, F3 and F4 can be programmed for the function of interest such as: PEAK, HOLD, RELEASE, TX DATA DATALOG, DISCHARGE, ZOOM.

MP6Plus allows you to enable and disable each channel and using the ZOOM function it is possible to display only the channel of interest in full screen. The instrument works with a resolution of ± 100.000 divisions and an accuracy better than 0.005% due to an internal 24-bit Sigma-Delta AD converter and a measurement control that is carried out for switching at a frequency equal to that of sampling: this system provides a better suppression of interference due to offset drift and to the connecting cables.

Nordic Transducer

Als Odde, DK-9560 Hadsund Denmark

Tel.: +45 98581444, Fax.: +45 98581866

E-mail: ntt@ntt.dk WEB: <http://www.ntt.dk>